


|   |  |  |   |                     |              |          |
|---|--|--|---|---------------------|--------------|----------|
| REMARK:   |  |  | REV.  | REVISIONS REC.      |              | DATE:    |
| 1.  |  |  | 1.  |                     |              |          |
| 2.  |  |  | 2.  |                     |              |          |
| 3.  |  |  | 3.  |                     |              |          |
| DRAWN BY  |  | TOLERANCES<br>X. X     ±0.3<br>X. XX    ±0.2<br>PIN PITCH: ±0.2<br>WALL THICKNESS: ±0.15 | ANGLE:  | MODEL NAME:         |              |          |
| CHECKED BY                                      |  |  | ±1°   | ER-2834 (5+5PIN)-1S |              |          |
| APPROVED BY                                     |  |  | UNIT:   | BOBBIN MATERIAL:    |              | UL REC.  |
|   |  |  | MM  | PHENOLIC            |              | UL 94V-0 |
| <div>Patron</div> <div>Passive Elektronik</div> |  |  | SCALE:  | PIN MATERIAL:       | REV.         |          |
|   |  |  | 2:1   | CP WIRE             | 0            |          |
|   |  |  |  | DRAWING NO:         | DATE:        |          |
|   |  |  |   | ER-2811             | 2010. 10. 10 |          |